

ALUMINIUM MAT ATF



TACTILE ALUMINIUM PROFILES IN HIGHLY DURABLE MAT

ENTRANCE ALU WITH TACTILE GUIDE STRIP ATF.

An entrance mat with tactile guide strip ATF (Aluminum Tactile Flooring) with contrasting color in two different profile heights. For best contrast, anthracite or black entrance mat is recommended with a white strip. Choose between ribbed or rubber inserts in the entrance mat.

An entrance mat in aluminium profiles provides a highly durable mat. The aluminium profiles are held together by stainless steel wire (Ø3 mm) and rubber separators (3-6 mm), which makes it easier to clean the

entrance recess as the mat can simply be rolled out of the way.

The profile 10 has been designed for entrances with normal traffic and the 17 for high traffic. The 22 is recommended for entrances with heavy traffic; it can handle shopping trolleys, wheelchairs, pushchairs, buggies, etc*.

Ribbed inserts (needle loom) for indoor (zone 2-3). Rubber inserts for covered outdoor entrances or for indoor use (zone 1-2).




Alternative solution for the caution tile when changing direction of the guide strip.

TECHNICAL DATA

Material:	Manufactured from aluminium profiles (1,5mm) with inserts and a sound insulating underlay. Profiles have alternating heights.				
Traffic	Normal to heavy load: average footfall < 1,000 - 2,500/day. e.g. offices, banks, schools, stores, public libraries				
	Colour/ Measurement	NCS	Art. no.		
	(+/- 1 mm)		10/17	17/22	22/27
ATF rubber	white, 230 mm	0,84	110 G-ATF	117 G-ATF	122 G-ATF
ATF rubber	black, 230 mm	0,15	110 G-ATF	117 G-ATF	122 G-ATF
ATF ribbed (needle loom)	black, 230 mm	0,16	117 R-ATF	117 R-ATF	122 R-ATF
Caution tile ATF	230 x 230 mm		110 DP-ATF	117 DP-ATF	122 DP-ATF

* Load: 2500 kg/m² (max. weight per wheel 150 kg, for trolleys or similar with 4 wheels = max. 600 kg/each).



ATF with ribbed inserts 7 profiles, 10/17.



ATF with rubber inserts 7 profiles, 17/22.



ATF with ribbed inserts 7 profiles, 22/27.