



**QUICK AND
EASY
INSTALLATION**

TACTILE GUIDANCE SYSTEMS POLYURETHANE TILES.

The polyurethane tactile guidance system from Matting is a tactile, visual product suitable for indoor and outdoor surfaces. These tiles are easy to detect thanks to the high level of visual contrast with the surface. The material and sandblasted surface mean that these non-slip panels are safe to walk on even in damp conditions. The tiles are bonded onto existing surfaces, installation on a dry surface (above +5°C). Can be placed in very busy areas.

TECHNICAL SPECIFICATIONS

| | Dimensions (+/- 1 mm) | Colour | NCS | Weight | Article no. |
|------------------|--|--------|------|-----------|-------------|
| Material: | UV-stable thermoplastic polyurethane Bayer Desmopan 3055DU. | | | | |
| Route tile | TPU 300 x 300 x 5 mm | White | 0,94 | 0,03 kg | 362685* |
| Route tile | TPU 300 x 300 x 5 mm | Black | 0,16 | 0,03 kg | 362686 |
| Route tile | TPU 300 x 300 x 5 mm | Grey | 0,63 | 0,03 kg | 362687 |
| Route tile | TPU 150 x 450 x 5 mm w tape | White | 0,94 | 0,0025 kg | 362720* |
| Route tile | TPU 150 x 450 x 5 mm w tape | Black | 0,16 | 0,0025 kg | 362721 |
| Route tile | TPU 150 x 450 x 5 mm wo tape | White | 0,94 | 0,0025 kg | 362730* |
| Route tile | TPU 150 x 450 x 5 mm wo tape | Black | 0,16 | 0,0025 kg | 362731 |
| Warning tile | TPU 413 x 450 x 5,5 mm | White | 0,94 | 0,062 kg | 362688* |
| Warning tile | TPU 413 x 450 x 5,5 mm | Black | 0,16 | 0,062 kg | 362689 |
| Warning tile | TPU 413 x 450 x 5,5 mm | Grey | 0,63 | 0,062 kg | 362690 |
| Lim Murexin TPU | | | | 10,2 kg | 362695 |

* Route tile TPU White is not UV-stable and recommended for indoor use only.

Two widths of
route tile 30 cm
and 15 cm.

Properties/advantages

- Clear difference from the adjacent surface in terms of colour and sound.
- Soundproofing.
- Wheelchair-friendly.
- Quick and easy installation.
- Easy to keep clean.
- Long service life.
- UV-stable (not valid for white).